

**TATA MOTORS**  
Connecting Aspirations



# Presenting the new TATA YODHA 1500

Bharosa Har Kadam



The reliable pickup  
for your business



## TECHNICAL SPECIFICATIONS

### ENGINE

|                    |                                 |
|--------------------|---------------------------------|
| Type               | TATA 4SP CR TCIC 4-cylinder BS4 |
| Capacity           | 2 956 cc                        |
| Max. Output        | 64 kW (85 hp) @ 3 000 r/min     |
| Max. Torque        | 250 Nm @ 1 000 - 2 000 r/min    |
| Fuel Tank Capacity | 45 l                            |

### CLUTCH & TRANSMISSION

|          |  |
|----------|--|
| Clutch   | Single Plate Dry Friction Type 260 mm dia            |
| Gearbox  | GBS76 - 5 / 4.1                                      |
| Steering | Synchromesh, 5 Forward + 1 Reverse<br>Power Steering |

### SUSPENSION

|               |   |
|---------------|---|
| Front         | Semi-elliptical Leaf Springs - 6 Leaves                         |
| Rear          | Innovative Two-stage Semi-elliptical<br>Leaf Springs - 9 Leaves |
| Anti-roll Bar | Front   |

### BRAKES

|       |                                 |
|-------|---------------------------------|
| Front | Hydraulic, Twin-pot Disc Brakes |
| Rear  | Drum Brakes                     |

### WHEELS & TYRES

|          |                      |
|----------|----------------------|
| Tyre     | 215 / 75 R 16 Radial |
| Rim Size | 16"                  |

### OVERALL VEHICLE DIMENSIONS

|                            |                                       |
|----------------------------|---------------------------------------|
| Width                      | 1 860 mm                              |
| Length                     | 5 350 mm                              |
| Height                     | 1 810 mm                              |
| Ground Clearance           | 210 mm                                |
| Wheelbase                  | 3 150 mm                              |
| Internal Load Body (L x B) | 2 550 mm (8.4 ft) x 1 750 mm (5.7 ft) |
| Turning Circle Radius      | 6 250 mm                              |

### WEIGHT

|             |          |
|-------------|----------|
| GVW         | 3 350 kg |
| Kerb Weight | 1 850 kg |
| Payload     | 1 500 kg |

### PERFORMANCE

|                      |         |
|----------------------|---------|
| Gradeability         | 30 %    |
| Restart Gradeability | 22 %    |
| Top Speed            | 80 km/h |
| Seating Capacity     | D + 1   |

### WARRANTY TERMS

|                            |  |
|----------------------------|--|
| Engine Oil Change Interval | 20 000 km                                  |
| Warranty (On Driveline)    | 3-year or 3 lakh km (Whichever is earlier) |



Flat bed type  
driver resting seats



Powerful & fuel efficient  
3 l bigger engine



Wide load body  
for higher earnings



Strong front & rear suspension  
with added leaves



High ground clearance



Warranty 3-year or 3 lakh km  
(Whichever is earlier)



Mileage: 14.06 km/l\*\*

**TATA MOTORS**

**SAMPOORNA SEVA**

AAPKE SAATH HAR KADAM

**TATA OK**    **TATA DELIGHT**    **LOYALTY REWARDS**    **TATA MOTORS INSURANCE**

**TATA KAVACH**    **TATA PROLIFE**    **TATA SURAKSHA**    **TATA GENUINE PARTS**

**TOLL FREE 1800 209 7979**

## TATA MOTORS

For more information, contact: Tata Motors Limited, 4<sup>th</sup> Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400093. Call: **1800 209 7979** (toll-free), Visit: [www.pickup.tatamotors.com](http://www.pickup.tatamotors.com) or SMS\*: <YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

\*As per terms & conditions in the operator's service manual.  
\*\* ₹ 3 per SMS or as per service provider. \*\* As per VRDE  
(Standard Test Conditions)